

Duckhams QXR 0W-30 PS

FULLY SYNTHETIC MOTOR OIL FOR PETROL & DIESEL ENGINES

PRODUCT DESCRIPTION

Duckhams QXR 0W-30 PS is a fully synthetic, high performance fuel-economy promoting engine oil, developed specifically for modern petrol and diesel PSA engines. Suitable for certain Peugeot and Citroën cars fitted with BlueHDi and PureTech engines.

SPECIFICATIONS

Recommended for vehicles requiring 0W-30 oils meeting the following specifications:
ACEA C2; PSA B71 2312

FEATURES AND BENEFITS

- Fully synthetic, high performance engine oil.
- Suitable for modern petrol and diesel vehicles.
- Developed specifically to promote fuel economy.

APPLICATIONS

CITROËN, DS, HONDA, HYUNDAI, KIA, PEUGEOT, SUZUKI, TOYOTA
May also be suitable for other vehicles. Always refer to your owner's handbook.

HEALTH, SAFETY AND ENVIRONMENT

- Based on available information, this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet.
- Safety Data Sheet available on request through your sales agent, or from the internet.
- Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.
- Protect the environment. Dispose of product and packaging in accordance with local regulations.

STORAGE AND HANDLING

- Packed lubricants should be stored under cover.
- Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress.
- Product should not be stored in direct sunlight or excessively high, or low, temperatures.
- Duckhams can provide professional advice on the storage of lubricants.

SHELF LIFE

- Expiry date 5 years after production date.
- Production date can be identified from the eight digit code printed on the bottle.
- YYYY.MM.DD



TYPICAL PHYSICAL CHARACTERISTICS

Typical Inspection Data:	Unit
Density @ 20°C	0.840 g/cm ³
Viscosity @ 100°C	9.70 cSt
Viscosity @ 40°C	54 cSt
Viscosity Index	167
Viscosity CCS @ -35°C	5900 cP
T.B.N.	6.0 mg KOH/g
Sulphated Ash Mass	0.6%
Zinc	0.10%
Calcium	0.13%
Phosphorus	0.08%
Colour	Brown
Flash Point	>210°C
Pour Point	-48°C

Typical physical characteristics are provided as an indication of properties based on current production data only, and should not be interpreted as a specification. Acceptable variation may occur during the manufacturing process without affecting the performance of the lubricant. This data can change without notification. Current version of this data supersedes all previous versions.