

Duckhams QXR 5W-30 GMCF

FULLY SYNTHETIC MOTOR OIL FOR PETROL ENGINES

PRODUCT DESCRIPTION

Duckhams QXR 5W-30 GMCF is a fully synthetic, high performance 5W-30 oil for modern petrol engines. Provides low speed pre-ignition (LSPI) protection, particularly for small displacement turbo-charged engines.

SPECIFICATIONS

Recommended for vehicles requiring 5W-30 oils meeting the following specifications:
API SN; ILSAC GF-5
Dexos 1:2015; GM 6094M and 4718M; Chrysler MS 6395; Ford WSS-M2C946-A

FEATURES AND BENEFITS

- Fully synthetic, high performance engine oil.
- Suitable for modern petrol vehicles.
- Provides low speed pre-ignition (LSPI) protection.
- Aids fuel economy.
- Quick cold weather starting for ultra-fast protection.

APPLICATIONS

CHEVROLET (GM), CHRYSLER, HUMMER (GM), OPEL/VAUXHALL, TOYOTA
May also be suitable for other vehicles. Always refer to your owner's handbook.

HEALTH, SAFETY AND ENVIRONMENT

- Based on available information, this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet.
- Safety Data Sheet available on request through your sales agent, or from the internet.
- Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.
- Protect the environment. Dispose of product and packaging in accordance with local regulations.

STORAGE AND HANDLING

- Packed lubricants should be stored under cover.
- Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress.
- Product should not be stored in direct sunlight or excessively high, or low, temperatures.
- Duckhams can provide professional advice on the storage of lubricants.

SHELF LIFE

- Expiry date 5 years after production date.
- Production date can be identified from the eight digit code printed on the bottle.
- YYYY.MM.DD



TYPICAL PHYSICAL CHARACTERISTICS

Property	Unit
Density @ 20°C	0.845 g/cm ³
Viscosity @ 100°C	11.1 cSt
Viscosity @ 40°C	61 cSt
Viscosity Index	177
Viscosity CCS @ -30°C	3600 cP
T.B.N.	8.3 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.13%
Phosphorus	0.08%
Colour	Brown
Flash Point	230°C
Pour Point	-33°C

Typical physical characteristics are provided as an indication of properties based on current production data only, and should not be interpreted as a specification. Acceptable variation may occur during the manufacturing process without affecting the performance of the lubricant. This data can change without notification. Current version of this data supersedes all previous versions.