

Duckhams Diesel Gard 10W-40 SHPD

SEMI SYNTHETIC MOTOR OIL FOR DIESEL ENGINES

PRODUCT DESCRIPTION

Duckhams Diesel Gard 10W-40 SHPD is a semi synthetic 10W-40 oil, suitable for high performance diesel engines including turbo charged and naturally aspirated. Ideal for mixed fleet-trucks.

SPECIFICATIONS

Recommended for vehicles requiring 10W-40 oils meeting the following specifications:

ACEA A3/B4, E7; API CI-4

MB 228.3; Volvo VDS-3; Renault RLD-2; MACK EO-N

FEATURES AND BENEFITS

- Semi synthetic engine oil.
- Suitable for high performance diesel engines including turbo charged and naturally aspirated.
- Ideal for mixed fleet-trucks.

APPLICATIONS

HONDA, ISUZU, LAND ROVER

May also be suitable for other vehicles. Always refer to your owner's handbook.

HEALTH, SAFETY AND ENVIRONMENT

- Based on available information, this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet.
- Safety Data Sheet available on request through your sales agent, or from the internet.
- Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.
- Protect the environment. Dispose of product and packaging in accordance with local regulations.

STORAGE AND HANDLING

- Packed lubricants should be stored under cover.
- Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress.
- Product should not be stored in direct sunlight or excessively high, or low, temperatures.
- Duckhams can provide professional advice on the storage of lubricants

SHELF LIFE

- Expiry date 5 years after production date.
- Production date can be identified from the eight digit code printed on the bottle.
- YYYY.MM.DD



TYPICAL PHYSICAL CHARACTERISTICS

Typical Inspection Data:	Unit
Density @ 20°C	0.865 g/cm ³
Viscosity @ 100°C	14.2 cSt
Viscosity @ 40°C	96 cSt
Viscosity Index	152
Viscosity CCS @ -25°C	5400 cP
T.B.N.	10.3mg KOH/g
Sulphated Ash Mass	1.5%
Zinc	0.13%
Calcium	0.37%
Phosphorus	0.11%
Colour	Dark Brown
Flash Point	>230°C
Pour Point	-33°C

Typical physical characteristics are provided as an indication of properties based on current production data only, and should not be interpreted as a specification. Acceptable variation may occur during the manufacturing process without affecting the performance of the lubricant. This data can change without notification. Current version of this data supersedes all previous versions.