

Duckhams Hypoid 75W-80 MTF

HIGH QUALITY GEAR OIL

PRODUCT DESCRIPTION

Duckhams Hypoid 75W-80 MTF is a fully synthetic manual transmission 75W-80 fluid with excellent bearing and gear protection and proven synchroniser performance.

SPECIFICATIONS

Recommended for certain BMW, Vauxhall/Opel, Mini, Land Rover, Honda, Volvo and MG applications and generally where a 75W-80, API GL-4 oil is specified.

BMW MTF LT-2; Ford M2C 186-A; GM 1940768; Mercedes Benz MB 235.10; MTF 94; Nissan MT-XZ TL (JR Type); Nissan MT-XZ; Special Honda MTF; Special Honda MTF II; Special Honda MTF-III; Tranself TRX, NFP, TRP, TRZ, Volvo 97308; API GL-4

FEATURES AND BENEFITS

- Fully synthetic manual transmission fluid.
- Provides excellent bearing and gear protection and proven synchroniser performance.
- Offers good low temperature performance, excellent cleanliness and robust corrosion protection.

HEALTH, SAFETY AND ENVIRONMENT

- Based on available information, this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet.
- Safety Data Sheet available on request through your sales agent, or from the internet.
- Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.
- Protect the environment. Dispose of product and packaging in accordance with local regulations.

STORAGE AND HANDLING

- Packed lubricants should be stored under cover.
- Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress.
- Product should not be stored in direct sunlight or excessively high, or low, temperatures.
- Duckhams can provide professional advice on the storage of lubricants

SHELF LIFE

- Expiry date 5 years after production date.
- Production date can be identified from the eight digit code printed on the bottle.
- YYYY.MM.DD



TYPICAL PHYSICAL CHARACTERISTICS

Typical Inspection Data:	Unit
Density @ 20°C	0.853 g/cm ³
Viscosity @ 100°C	8.7 cSt
Viscosity @ 40°C	50 cSt
Calcium	0.29%
Phosphorus	0.05%
Colour	Brown
Pour Point	-39°C

Typical physical characteristics are provided as an indication of properties based on current production data only, and should not be interpreted as a specification. Acceptable variation may occur during the manufacturing process without affecting the performance of the lubricant. This data can change without notification. Current version of this data supersedes all previous versions.