

Duckhams Hypoid S 75W-90 GL-5

SUPERIOR QUALITY GEAR OIL

PRODUCT DESCRIPTION

Duckhams Hypoid S 75W-90 GL-5 is a semi synthetic differential oil suitable for modern five and six speed gear boxes and differentials where a 75W-90, 75W-85, 80W-90 or 85W-90 API GL-5, GL-4 oil is specified.

SPECIFICATIONS

Recommended for vehicles where a 75W-90, 80W-90, 85W-90, API GL-5 oil is specified.

SAE 75W, SAE 75W-90, SAE 80W, SAE 80W-90, SAE 85W, SAE 85W-90, SAE 90

FEATURES AND BENEFITS

- Semi synthetic differential oil.
- Suitable for modern five and six speed gear boxes and differentials.
- Offers superior gear protection and excellent anti-wear properties.

HEALTH, SAFETY AND ENVIRONMENT

- Based on available information, this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet.
- Safety Data Sheet available on request through your sales agent, or from the internet.
- Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.
- Protect the environment. Dispose of product and packaging in accordance with local regulations.

STORAGE AND HANDLING

- Packed lubricants should be stored under cover.
- Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress.
- Product should not be stored in direct sunlight or excessively high, or low, temperatures.
- Duckhams can provide professional advice on the storage of lubricants

SHELF LIFE

- Expiry date 5 years after production date.
- Production date can be identified from the eight digit code printed on the bottle.
- YYYY.MM.DD



TYPICAL PHYSICAL CHARACTERISTICS

| Typical Inspection Data: | Unit |
|--------------------------|-------------------------|
| Density @ 20°C | 0.870 g/cm ³ |
| Viscosity @ 100°C | 15.5 cSt |
| Viscosity @ 40°C | 100 cSt |
| Phosphorus | 0.02% |
| Colour | Light Straw |
| Pour Point | -42°C |

Typical physical characteristics are provided as an indication of properties based on current production data only, and should not be interpreted as a specification. Acceptable variation may occur during the manufacturing process without affecting the performance of the lubricant. This data can change without notification. Current version of this data supersedes all previous versions.