

Duckhams C-Trans

HIGH QUALITY CVT FLUID FOR MODERN CARS

PRODUCT DESCRIPTION

Duckhams C-Trans is a high performance CVT fluid for use in wide range of vehicle makes. Provides excellent anti-wear as well as belt & chain friction performance.

SPECIFICATIONS

Recommended for certain VW, Audi, Seat, Ford, Honda, Jeep, Mazda, Mercedes-Benz, Mini, Mitsubishi, Nissan, Renault, Subaru, Suzuki, Vauxhall, Opel & Toyota CVT transmissions.

GM DEX-CVT; GM 1940713; GM 1940714; Ford M2C928-A; WSS-M2C933-A; Mercon C; Nissan NS-1 CVT fluid; Nissan NS-2 CVT fluid; Nissan NS-3 CVT fluid; Mercedes Benz MB 236.20; MG Rover ATF EM-CVT; Subaru Lineartronic High Torque CVT Fluid; Subaru Lineartronic CV-30; Subaru Lineartronic Chain CVTF II; Subaru Lineartronic Chain CVT fluid; Subaru iCVT; Subaru NS-2; BMW/Mini Cooper EZL-799 (ZF CVT V1); Honda HCF-2; Hyundai/Kia CVT-J1; Hyundai/ Kia SP III (CVT model); Mazda JWS 3320; Dodge/ Jeep; Mopar CVTF +4; Toyota CVT WS (Prius eCVT only); Toyota CVT TC; Toyota CVT FE; Renault Elfmatic CVT; Suzuki CVT Green 1; Suzuki CVT Green 2; Suzuki CVTF TC; Suzuki CVTF 3320; Audi/VW VW G 052 180 A2/ TL 521 80; VW G 052 516/ TL 521 16; Idemitsu CVTS-EX1; Daihatsu Ammix CVT Fluid DC; Daihatsu Ammix CVT Fluid DFC; Daihatsu Fluid TC; Daihatsu Ammix CVT Fluid DFE; Mitsubishi DiaQueen CVTF J1; DiaQueen CVTF J4; DiaQueen CVTF J4+

FEATURES AND BENEFITS

- Fully synthetic high performance CVT fluid.
- Suitable for use in wide range of vehicle makes, except hybrid transmissions.
- Provides excellent anti-wear as well as belt & chain friction performance.

HEALTH, SAFETY AND ENVIRONMENT

- Based on available information, this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet.
- Safety Data Sheet available on request through your sales agent, or from the internet.
- Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.
- Protect the environment. Dispose of product and packaging in accordance with local regulations.

STORAGE AND HANDLING

- Packed lubricants should be stored under cover.
- Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress.
- Product should not be stored in direct sunlight or excessively high, or low, temperatures.
- Duckhams can provide professional advice on the storage of lubricants

SHELF LIFE

- Expiry date 5 years after production date.
- Production date can be identified from the eight digit code printed on the bottle.
- YYYY.MM.DD



TYPICAL PHYSICAL CHARACTERISTICS

Typical Inspection Data:	Unit
Density @ 20°C	0.845 g/cm ³
Viscosity @ 100°C	7.3 cSt
Viscosity @ 40°C	35 cSt
Phosphorus	0.04%
Colour	Brown
Pour Point	-42°C

Typical physical characteristics are provided as an indication of properties based on current production data only, and should not be interpreted as a specification. Acceptable variation may occur during the manufacturing process without affecting the performance of the lubricant. This data can change without notification. Current version of this data supersedes all previous versions.