

Duckhams QS 5W-30 DX

FULLY SYNTHETIC MOTOR OIL FOR PETROL & DIESEL ENGINES

PRODUCT DESCRIPTION

Duckhams QS 5W-30 DX is a fully synthetic, high performance 5W-30 mid SAPS oil for modern petrol and diesel vehicles including those fitted with exhaust after-treatment units that require an ACEA C2, C3 grade.

SPECIFICATIONS AND APPROVALS

Recommended for vehicles requiring 5W-30 oils meeting the following specifications:
ACEA C2, C3; API SN/CF; dexos 2; VW 505 00, VW 505 01; MB 229.51, MB 229.31
MB-Approval 229.52

FEATURES AND BENEFITS

- Fully synthetic, high performance, mid-SAPS engine oil.
- Suitable for modern petrol and diesel vehicles.
- For modern MB and GM vehicles including those operating with long life service intervals.
- Do not mix this oil with other types of oil, as the requirement of exhaust after-treatment protection will no longer be guaranteed.

APPLICATIONS

AUDI, HONDA, HYUNDAI, KIA, MERCEDES BENZ, MINI, OPEL/VAUXHALL
May also be suitable for other vehicles. Always refer to your owner's handbook.

HEALTH, SAFETY AND ENVIRONMENT

- Based on available information, this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet.
- Safety Data Sheet available on request through your sales agent, or from the internet.
- Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.
- Protect the environment. Dispose of product and packaging in accordance with local regulations.

STORAGE AND HANDLING

- Packed lubricants should be stored under cover.
- Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress.
- Product should not be stored in direct sunlight or excessively high, or low, temperatures.
- Duckhams can provide professional advice on the storage of lubricants.

SHELF LIFE

- Expiry date 5 years after production date.
- Production date can be identified from the eight digit code printed on the bottle.
- YYYY.MM.DD



TYPICAL PHYSICAL CHARACTERISTICS

Typical Inspection Data:	Unit
Density @ 20°C	0.850 g/cm ³
Viscosity @ 100°C	12.0 cSt
Viscosity @ 40°C	72 cSt
Viscosity Index	164
Viscosity CCS @ -30°C	6000 cP
T.B.N.	6.4 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.18%
Phosphorus	0.08%
Colour	Brown
Flash Point	>230°C
Pour Point	-39°C

Typical physical characteristics are provided as an indication of properties based on current production data only, and should not be interpreted as a specification. Acceptable variation may occur during the manufacturing process without affecting the performance of the lubricant. This data can change without notification. Current version of this data supersedes all previous versions.