



TECHNICAL DATA SHEET

DUCKHAMS CLASSIC Hypoid 85W-140 API GL-5

GENERAL DESCRIPTION

Duckhams Classic Hypoid 85W-140 API GL-5, is designed for differential units and manual classic and vintage gearboxes where high extreme pressure protection is required in gear sets requiring this viscosity and API performance level.

FEATURES AND BENEFITS

Duckhams Hypoid 85W-140 API GL-5 is predominantly for use in classic and vintage cars' differential units
Duckhams Hypoid 85W-140 API GL-5 is also suitable for use in many gearboxes where a higher level of extreme pressure protection is required and where SAE 85W-140 viscosity is indicated.

PHYSICAL CHARACTERISTICS

Density at 15°C, kg/litre	0.905
Viscosity, Kinematic, cSt at 40°C	188 to 352 (ISO VG 320)
Viscosity, Kinematic, cSt at 100°C	Approx. 27
Viscosity Index	>98



TECHNICAL DATA SHEET

SPECIFICATIONS AND APPROVALS

SAE 85W-140; API GL-5

HEALTH, SAFETY AND ENVIRONMENT

There are no unusual hazards in using most lubricating oils and greases provided ordinary care is taken to avoid frequent or prolonged skin contact with fresh or used products. The user should ensure that good working practices are maintained at all times.

STORAGE, HANDLING AND DISPOSAL

All packed lubricants should preferably be stored under cover. Where outside storage of drums is unavoidable, they should be placed horizontal in order to avoid water contamination. Bulk tanks are best located under cover. Duckhams can provide professional advice on the location and installation of tanks

AVAILABLE PACK SIZES

1 litre can, 20 litre pail.

