

Duckhams QS 5W-40 MRV

FULLY SYNTHETIC MOTOR OIL FOR PETROL & DIESEL ENGINES

PRODUCT DESCRIPTION

Duckhams QS 5W-40 MRV is a fully synthetic, high performance 5W-40 oil, for petrol and diesel vehicles including those with fuel injected and multivalved engines.

SPECIFICATIONS AND APPROVALS

Recommended for vehicles requiring 5W-40 oils meeting the following specifications:

ACEA A3/B4; API SN/CF

MB 226.5, MB 229.1; RN0700, RN0710; PORSCHE A40

Approved under VW standard 502 00 and VW standard 505 00; MB-Approval 229.3*

FEATURES AND BENEFITS

- Fully synthetic, high performance engine oil.
- Suitable for petrol and diesel vehicles.
- Low viscosity to give fast oil flow on start up.

APPLICATIONS

AUDI, MERCEDES BENZ, OPEL/VAUXHALL, PEUGEOT, RENAULT, SEAT, SKODA, VOLKSWAGEN

May also be suitable for other vehicles. Always refer to your owner's handbook.

HEALTH, SAFETY AND ENVIRONMENT

- Based on available information, this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet.
- Safety Data Sheet available on request through your sales agent, or from the internet.
- Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.
- Protect the environment. Dispose of product and packaging in accordance with local regulations.

STORAGE AND HANDLING

- Packed lubricants should be stored under cover.
- Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress.
- Product should not be stored in direct sunlight or excessively high, or low, temperatures.
- Duckhams can provide professional advice on the storage of lubricants.

SHELF LIFE

- Expiry date 5 years after production date.
- Production date can be identified from the eight digit code printed on the bottle.
- YYYY.MM.DD



TYPICAL PHYSICAL CHARACTERISTICS

Typical Inspection Data:	Unit
Density @ 20°C	0.853 g/cm ³
Viscosity @ 100°C	15.0 cSt
Viscosity @ 40°C	94 cSt
Viscosity Index	168
Viscosity CCS @ -30°C	6200 cP
T.B.N.	10.0 mg KOH/g
Sulphated Ash Mass	1.1%
Zinc	0.13%
Calcium	0.34%
Phosphorus	0.11%
Colour	Brown
Flash Point	>210°C
Pour Point	-39°C

Typical physical characteristics are provided as an indication of properties based on current production data only, and should not be interpreted as a specification. Acceptable variation may occur during the manufacturing process without affecting the performance of the lubricant. This data can change without notification. Current version of this data supersedes all previous versions.