

## Duckhams Diesel Gard Pro 10W-40 LA

FULLY SYNTHETIC MOTOR OIL FOR DIESEL ENGINES

### PRODUCT DESCRIPTION

Duckhams Diesel Gard Pro 10W-40 LA is a fully synthetic, low SAPS 10W-40 oil to protect both engine and emission control equipment. Suitable for high performance diesel engines including turbo charged and naturally aspirated.

### SPECIFICATIONS

Recommended for vehicles requiring 10W-40 oils meeting the following specifications:  
ACEA E6, E7; Volvo VDS-3; RVI RLD-2; MTU Type 3.1;  
MACK EO-N; MAN 3477; MB 228.51

### FEATURES AND BENEFITS

- Fully synthetic, low SAPS engine oil.
- Suitable for high performance diesel engines including turbo charged and naturally aspirated.
- Protects both engine and emission control equipment.

### APPLICATIONS

ISUZU, MERCEDES BENZ, NISSAN

May also be suitable for other vehicles. Always refer to your owner's handbook.

### HEALTH, SAFETY AND ENVIRONMENT

- Based on available information, this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet.
- Safety Data Sheet available on request through your sales agent, or from the internet.
- Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.
- Protect the environment. Dispose of product and packaging in accordance with local regulations.

### STORAGE AND HANDLING

- Packed lubricants should be stored under cover.
- Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress.
- Product should not be stored in direct sunlight or excessively high, or low, temperatures.
- Duckhams can provide professional advice on the storage of lubricants

### SHELF LIFE

- Expiry date 5 years after production date.
- Production date can be identified from the eight digit code printed on the bottle.
- YYYY.MM.DD



### TYPICAL PHYSICAL CHARACTERISTICS

Typical Inspection Data:	Unit
Density @ 20°C	0.856 g/cm <sup>3</sup>
Viscosity @ 100°C	14.2 cSt
Viscosity @ 40°C	96 cSt
Viscosity Index	150
Viscosity CCS @ -25°C	6400 cP
T.B.N.	10.0 mg KOH/g
Sulphated Ash Mass	0.98%
Zinc	0.09%
Calcium	0.26%
Phosphorus	0.08%
Colour	Brown
Flash Point	>200°C
Pour Point	-33°C

Typical physical characteristics are provided as an indication of properties based on current production data only, and should not be interpreted as a specification. Acceptable variation may occur during the manufacturing process without affecting the performance of the lubricant. This data can change without notification. Current version of this data supersedes all previous versions.