

Duckhams QXR 10W-50 MS

FULLY SYNTHETIC MOTOR OIL FOR PETROL & DIESEL ENGINES

PRODUCT DESCRIPTION

Duckhams QXR 10W-50 MS is a fully synthetic engine oil, specially developed for high performance vehicles with natural aspiration or turbocharging engines. Offers excellent friction protection even at high revolutions.

SPECIFICATIONS

Recommended for vehicles requiring 10W-50 oils meeting the following specifications:
ACE A3/B4; API SN

FEATURES AND BENEFITS

- Fully synthetic high performance engine oil.
- Suitable for petrol and diesel engines.
- Specially developed for high performance vehicles with natural aspiration or turbocharging engines.
- Offers excellent friction protection even at high revolutions.

APPLICATIONS

INFINITI, MITSUBISHI, NISSAN, SUBARU

May also be suitable for other vehicles. Always refer to your owner's handbook.

HEALTH, SAFETY AND ENVIRONMENT

- Based on available information, this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet.
- Safety Data Sheet available on request through your sales agent, or from the internet.
- Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.
- Protect the environment. Dispose of product and packaging in accordance with local regulations.

STORAGE AND HANDLING

- Packed lubricants should be stored under cover.
- Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress.
- Product should not be stored in direct sunlight or excessively high, or low, temperatures.
- Duckhams can provide professional advice on the storage of lubricants.

SHELF LIFE

- Expiry date 5 years after production date.
- Production date can be identified from the eight digit code printed on the bottle.
- YYYY.MM.DD



TYPICAL PHYSICAL CHARACTERISTICS

| Typical Inspection Data: | Unit |
|--------------------------|-------------------------|
| Density @ 20°C | 0.850 g/cm ³ |
| Viscosity @ 100°C | 16.9 cSt |
| Viscosity @ 40°C | 111 cSt |
| Viscosity Index | 166 |
| Viscosity CCS @ -25°C | 5000 cP |
| T.B.N. | 10.1 mg KOH/g |
| Sulphated Ash Mass | 1.0% |
| Zinc | 0.11% |
| Calcium | 0.27% |
| Phosphorus | 0.10% |
| Colour | Brown |
| Flash Point | >230°C |
| Pour Point | -39°C |

Typical physical characteristics are provided as an indication of properties based on current production data only, and should not be interpreted as a specification. Acceptable variation may occur during the manufacturing process without affecting the performance of the lubricant. This data can change without notification. Current version of this data supersedes all previous versions.